



MB300

Pocket Scanner

CHAMPTEK[®]
We value your ID's

Introduction

MB300 is a brand new compact design which is especially for ticketing, stocktaking or logistic market. With its tiny body, it can be easily carried in pocket or bag for mobility application. It can easily connect to the mobile device as a host by Bluetooth technology and transfer all the scanned data immediately to the corresponding application program.

With its auto-shuttle-emulation-like smart detection that offers superior decoding on a reading speed up to 500 scans per second and up to 500mm reading depth for the majority of 1D barcodes, the scanner delivers excellent decoding performance.

MB300 is absolutely a high performance compact barcode scanner that provides the most cost-effective solutions in the market. It is perfectly suitable and definitely the best choice for the application with mobile devices.

Features

- Bright 1" OLED Display
- Easy Control With 3 Scrolling Buttons
- Instant Response by Vibration
- Rechargeable Li-Poly Battery With User Compartment for Easy Replacement
- Data Transmission via Bluetooth V2.1+EDR(Class2, HID/SPP)
- High Performance with CCD/ 2D / Laser Scan Module
- Large Data Storage of 8 MB Memory
- Reliable Design to Fulfill 1.5m Meter Drop Threshold, IP54-Rated
- Easy Development in AP

MB300

Specifications

• System

Micro Processor	32-bit
Operating Platform	Proprietary
Flash Memory	512 Kbyte program. 8 M bytes user data that can save over 100,000 items of 50 bytes barcode data.
RAM Memory	128 Kbytes
Display Size	0.96" OLED 128x64 dots Monochrome for MB300 series.
Input Keys	3 buttons, include 1. scan and confirm trigger button 2. upward scroll button 3. downward scroll button
Indicator	1. LED x 1 2. Beeper x 1 3. Vibration motor x 1

• Power Source

Battery	Lithium-Polymer (3.7V DC, 550mAh)
Battery Charging	via Micro USB connector

• Physical Characteristics

Dimensions	41.8mm x 89.9mm x 23.6mm (W x D x H)
Weight	Designed to be approx. 70 g
Available color	Black cover and dark gray bottom cases
Hanger	1 Hanger Hole
Protection	IP54 sealing protection
Drop Spec.	1.5m (5 feet)

• Data Input

4 Options: by respective rollout schedule.

One of the barcode scanners

(1) CCD 1D Scanner

(2) 2D imager scanner

(3) Laser 1D scanner

(4) RFID(NFC) Reader, supports ISO14443A standard, ISO14443B, ISO15693, Felica™, Mifare Classic Mifare UL, Topaz, NFC-P2P

• Communication Interface

Wired	Micro USB V2.0 (for Power charge and Batch data transmission)
-------	--

Wireless	Bluetooth 2.1 + EDR
----------	---------------------

• Functions

Standby Duration	Over 3 months
Scan per charge	10,000 scans [BT off] / 5000 scans [BT On] under normal operating conditions after battery full charged.
Low Battery Alert	Battery levels are indicated by the LED illuminating color
Data Handling	Able to be chosen as on-line (via BT or Wifi) or off-line (batch) mode.
Off-line Mode	Can save over 100,000 items of 50 bytes barcode data.
Indication combination	Can be configured as (1)LED indication (2)LED indication + Beep (3)LED indication + Scan Review (4)LED indication + Vibration (5)LED indication + Beep + Vibration (6)LED indication + Scan Review + Beep (7)LED indication + Scan Review + Vibration or (8)LED indication + Scan Review + Beep + Vibration
Compatibility	Customers can easily develop AP on different OS.

Due to Champtek's continuing product improvement programs, specifications and features are subjected to change without prior notices.